



HIPERPOWER HPU-5M730

NEW RELEASE!



Features:

- 4 x USB port + 1 x mobile device charger port.
- 4 x independent 12V rails
- Support NVIDIA SLI & QUAD-SLI.
- Certified up to Nvidia GeForce 8800 GTX
- Complies with latest ATX12V v2.2 / EPS12V v2.91 form factors.
- Fully compatible with AMD 64 bit and Intel LGA processors.
- Active PFC.
- Extender™
- Gold plated connectors for minimum power loss and optimal conductivity.
- PCI-E, SATA, Molex with EZ-Grip, floppy, P8 & P4 connectors.
- Modular power cord (European model only).
- 20 dB(A) under normal load.



Specification	Description	HPU-5M730
Wattage	Rated Wattage	730 Watts
	Peak Load	930 Watts
Rear Fan	80mm	1800 - 3800 R.P.M.
	Bearing Type	dual ball bearing
Input Parameter	Voltage Range	100 - 240V
	Current	10A
	Frequency Range	50 - 60 Hz
Form Factor	ATX12V	V 2.2
	EPS 12V	V 2.91
Efficiency	Average	> 80%
Output Load Regulation	+12V1 & +12V2 & +12V3 & +12V4	< 672W
	+3.3V & +5V	< 170W
	+3.3V, +5V & +12V	< 715W
PFC	Power Factor Correction	Active
Unit Size	Dimension	180 x 150 x 86 mm
		7.1" x 5.9" x 3.4"
Warranty		3 years

© 2007 HIPER is a registered trademark of High Performance Enterprise PLC. All other trademarks are the property of their respective owners. June 2007. All data subject to be changed.